



## Model: CSP-A1410

### Inline Cabinet Fan

#### Standard Construction Features:

- Galvanized steel housing - Sound absorbing insulation - Outlet duct collar with integral spring loaded back draft damper - Forward curved wheel - Plug type disconnect - Adjustable mounting brackets - Square duct connection - Dual galvanized steel scroll design - Field rotatable discharge

#### Stock Notes

- Units are stocked with 115/60/1 motors
- All CSP fans require 5 watt speed controller, Model CSP-A1050 and CSP-A1401 require 10W speed controller

#### Available Accessories

- Wall and discharge accessories
- Vibration isolation kit
- Speed control

Dimensional	
Quantity	1
Weight w/o Acc's (lb)	59
Weight w/ Acc's (lb)	59

Motor	
Motor Mounted	Yes
** Input Watts (W)	845
Voltage/Cycle/Phase	115/60/1
Enclosure	ODP

Model	Control Voltage	RPM	Amps*	Max. Input Watts*	CFM / Static Pressure in Inches wg												
					0	0.1	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1.0	1.25	1.5	
CSP-A1410		1450	7.80	871	CFM	1584	1543	1533	1483	1439	1395	1345	1293	1238	1181		
					Sones	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	4.0	4.0		
					Watts*	870.8	837.9	829.9	788.2	751.0	728.3	696.3	661.8	628.8	595.9		