



## Model: CSP-A710

### Inline Cabinet Fan

#### Standard Construction Features:

- Galvanized steel housing - Sound absorbing insulation - Outlet duct collar with integral back draft damper - Forward curved wheel - Plug type disconnect - Adjustable mounting brackets - Square duct connection - Field rotatable discharge

#### Stock Notes

- Units are stocked with 115/60/1 motors
- All CSP fans require 5 watt speed controller, Model CSP-A1050 and CSP-A1401 require 10W speed controller

#### Available Accessories

- Wall and discharge accessories
- Vibration isolation kit
- Speed control

Dimensional	
Quantity	1
Weight w/o Acc's (lb)	36
Weight w/ Acc's (lb)	36

Motor	
Motor Mounted	Yes
** Input Watts (W)	322
Voltage/Cycle/Phase	115/60/1
Enclosure	ODP

Model	Control Voltage	RPM	Amps*	Max. Input Watts*	CFM / Static Pressure in Inches wg												
					0	0.1	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1.0	1.25	1.5	
CSP-A710		1080	4.40	333	CFM	737	698	688	635	567	475	334					
					Sones	2.5	2.5	2.5	2.5	2.0	2.0	2.0					
					Watts*	332.5	324.1	322.0	310.8	295.8	277.4	255.2					