



Model: CSP-A900

Inline Cabinet Fan

Standard Construction Features:

- Galvanized steel housing - Sound absorbing insulation - Outlet duct collar with integral spring loaded back draft damper - Forward curved wheel - Plug type disconnect - Adjustable mounting brackets - Square duct connection - Dual galvanized steel scroll design - Field rotatable discharge

Stock Notes

- Units are stocked with 115/60/1 motors
- All CSP fans require 5 watt speed controller, Model CSP-A1050 and CSP-A1401 require 10W speed controller

Available Accessories

- Wall and discharge accessories
- Vibration isolation kit
- Speed control

Dimensional	
Quantity	1
Weight w/o Acc's (lb)	59
Weight w/ Acc's (lb)	59

Motor	
Motor Mounted	Yes
** Input Watts (W)	318
Voltage/Cycle/Phase	115/60/1
Enclosure	ODP

Model	Control Voltage	RPM	Amps*	Max. Input Watts*	CFM / Static Pressure in Inches wg												
					0	0.1	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1.0	1.25	1.5	
CSP-A900		895	2.91	318	CFM	930	875	865	811	755	686	558	411	290			
					Sones	0.4	0.3	0.3	0.3	0.4	0.9	1.4	2.0	2.5			
					Watts*	318.3	308.1	305.5	297.7	289.8	278.0	260.9	245.7	225.5			