





Model: SP-B110

Ceiling Exhaust Fan

Standard Construction Features:

- Corrosion resistant galvanized steel scroll and housing - White designer non-yellowing grille - Round outlet duct collar with integral backdraft damper - Single inlet forward curved wheel - Plug type disconnect - Adjustable mounting brackets

Stock Notes

- Units are stocked with 115/60/1 motors
- Plug-in disconnect switch included
- Integral backdraft damper
- All SP fans require 5W Speed Controller

Available Accessories

- Speed controls
- Wall and discharge accessories

Dimensional								
Quantity	1							

10

10

Weight w/o Acc's (lb)

Weight w/ Acc's (lb)

-13.875 →

MOUNTING

BRACKET

Motor									
Motor Mounted	Yes								
** Input Watts (W)	80								
Voltage/Cycle/Phase	115/60/1								
Enclosure	ODP								

Model SP-B Performance																	
Model	ENERGY STAR®	HVI	Continuous Ventilation Compatible	RPM	Amps*	Max. Input Watts*		CFM / Static Pressure in Inches wg									
								0	0.1	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1.0
SP-B110		+	•	950	1.14	80.2	CFM	133	114	110	97	95	94	91	85	72	50
			_				Sones	1.5	1.5	1.5	2.0	2.0	2.0	3.0	3.5	4.0	4.5