





Model: SP-B150

Ceiling Exhaust Fan

Standard Construction Features:

- Corrosion resistant galvanized steel scroll and housing - White designer non-yellowing grille - Round outlet duct collar with integral backdraft damper - Single inlet forward curved wheel - Plug type disconnect - Adjustable mounting brackets

Stock Notes

- Units are stocked with 115/60/1 motors
- Plug-in disconnect switch included
- Integral backdraft damper
- All SP fans require 5W Speed Controller

Available Accessories

- Speed controls
- Wall and discharge accessories

MOUNTING	13.875 – Ø6	11.5 1.25				
BRACKET						
2.0.0						
·						

Dimensional								
Quantity	1							
Weight w/o Acc's (lb)	10							
Weight w/ Acc's (lb)	10							

Motor								
Motor Mounted	Yes							
** Input Watts (W)	128							
Voltage/Cycle/Phase	115/60/1							
Enclosure	ODP							

Model SP-B Performance																	
	ENERGY STAR®	HVI	Continuous Ventilation Compatible	RPM	Amps*	Max. Input Watts*		CFM / Static Pressure in Inches wg									
								0	0.1	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1.0
SP-B150				1050	1.70	128	CFM	160	156	155	154	152	149	147	138	123	92
							Sones	2.5	2.5	2.5	3.0	3.5	3.5	4.0	4.5	4.5	5.0